

**MSDS DATA SHEET**

Created on 10/03/2003

Part Number: 1051055

XX

CHEMISTRI 10/03/03

DISPLAY MATERIAL SAFETY DATA SHEET 09:02:48

SCREEN QA06\_\_ KEY 0000939321,0000000018\_\_\_\_\_

FID#: 00181855 VER-DT: 03/30/90

-----  
SECTION 01: CHEMICAL PRODUCT & COMPANY ID  
-----

PRODUCT PRIMARY NAME: PRESERVATONE VINYL TOP DRESSING  
PLANT SYNONYMS: GOODWRENCH PRESERVATONE VINYL TOP DRESSING  
> MAGIC MIRROR PRESERVATONE  
> PRESERVATONE VINYL TOP DRESSING  
> 1051054  
> 1051055  
> 40570  
> 40571

MSDS SIGNED BY NAME: JOHN F. COLEMAN PH.D.  
MSDS SIGNED BY TITLE: DIRECTOR OF TECHNOLOGY

SAFE USE CATEGORY AND DESCRIPTION: 03 -SOLVENTS - FLASH POINT: > 100 F  
LAST UPDATED DATE: 1991-05-01

MANUFACTURER'S ID (MID): 000506364  
MANUFACTURER'S NAME: U.S. CHEMICAL & PLASTICS INC  
MANUFACTURER'S EMERGENCY PHONE NUMBER/TEXT: US 800-424-9300  
MANUFACTURER'S MAILING ADDRESS:  
ALCO INDUSTRIES, PO BOX 88  
2290 ZIMMERMAN ROAD SE  
GNADENHUTTEN OH 44629  
US

CHEMICAL FAMILY NAME: MIXTURE, SEE SECTION 2.

MOLECULAR FORMULA: N/A

-----  
SECTION 02: COMPOSITION & INGREDIENT INFO  
-----

CAS#	FORMULATION	W/V	CHEMICAL NAME
000107211	R 1.0000/ 2.0000%	W	ETHYLENE GLYCOL
000111900	R 4.0000/ 6.0000%	W	ETHANOL, 2-(2-ETHOXYETHOXY)-
001336216	< 0.0000/ 0.2000%	W	AMMONIUM HYDROXIDE
007732185	R 55.0000/ 58.0000%	W	WATER
027138314	R 1.0000/ 3.0000%	W	Propanol, oxybis-, dibenzoate
989922746	< 0.0000/ 1.0000%	W	ADDITIVES
989958216	R 34.0000/ 38.0000%	W	STYRENE ACRYLIC LATEX

THRESHOLD LIMIT VALUE: N/A

PERMISSIBLE EXPOSURE LIMIT: N/A

-----  
SECTION 03: HAZARDS IDENTIFICATION  
-----

SKIN PRIMARY ENTRY ROUTE INDICATOR = Y  
EYE PRIMARY ENTRY ROUTE INDICATOR = N  
INHALATION PRIMARY ENTRY ROUTE INDICATOR = Y  
INGESTION PRIMARY ENTRY ROUTE INDICATOR = Y

PRIMARY ROUTES OF ENTRY TEXT: INHALATION, SKIN CONTACT, INGESTION

EFFECTS OF OVEREXPOSURE: DO NOT INGEST. IRRITANT WHEN IN CONTACT WITH OPEN OR ABRADED SKIN.

SECTION 3 - OTHER INFORMATION: N/A

-----  
SECTION 04: FIRST AID MEASURES  
-----

EMERGENCY FIRST AID PROCEDURES - GENERAL: SWALLOWED: REMOVE VICTIM FROM EXPOSURE TO WELL-VENTILATED AREA. MAKE COMFORTABLY WARM BUT NOT HOT. VOMITING. IF CONSCIOUS, GIVE VICTIM WATER TO DRINK. CALL A PHYSICIAN. EYE CONTACT: FLUSH PROMPTLY WITH EXCESS WATER. CALL A PHYSICIAN. SKIN CONTACT: WASH PROMPTLY WITH SOAP AND EXCESS WATER.

-----  
SECTION 05: FIRE-FIGHTING MEASURES  
-----

EXTINGUISHING MEDIA: CO2, DRY CHEMICALS, FOAM

SPECIAL FIRE FIGHTING PROCEDURES: FIGHT LIKE A FUEL OIL FIRE. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. FIREFIGHTERS WEAR MSHA/NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CLOSED CONTAINERS EXPOSED TO FIRE TEMPERATURES MAY RUPTURE

NFPA CODES:

NFPA HEALTH CODE = 2

NFPA REACTIVITY CODE = 1

FLASH POINT TEMPS: 87.00C/ 190.00F

FLASH POINT TEXT: 190F CC SETA

FLASH POINT METHOD: SETA

-----  
SECTION 06: ACCIDENTAL RELEASE MEASURES  
-----

SPILL OR LEAK PROCEDURES: PICK UP LARGE SPILLS WITH INERT ABSORBENT LIKE VERMICULITE OR SAND, AND PLACE IN A PROPER CONTAINER FOR DISPOSAL. WASH AND CLEAN UP SMALL SPILLS WITH WATER AND DETERGENTS.

-----  
SECTION 07: HANDLING AND STORAGE  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP AWAY FROM EXTREME HEAT, OPEN FLAME, OR OTHER SOURCES OF IGNITION. DO NOT STORE ABOVE 100F. USE WITH ADEQUATE VENTILATION. DANGER: HARMFUL OR FATAL IF SWALLOWED| CONTAINS PETROLEUM DISTILLATES| COMBUSTIBLE| AVOID BREATHING VAPORS|

SECTION 7 - OTHER INFORMATION: REMOVE WAX FROM SURFACE PRIOR TO WELDING.

-----  
SECTION 08: EXPOSURE CONTROLS - PROTECTION  
-----

EYE PROTECTION: GOGGLES TO PROTECT AGAINST SPLASHES

RESPIRATORY PROTECTION: VENTILATE WITH AIR FLOW.

SHOULD BE AVAILABLE.

SECTION 8 - OTHER INFORMATION: N/A

PROTECTIVE GLOVES (SPECIFY TYPE): NEOPRENE OR EQUIVALENT

-----  
SECTION 09: PHYSICAL & CHEMICAL PROPERTIES  
-----

BOILING POINT TEMPS: 99.00C/ 211.00F  
BOILING POINT TEXT: 211F

SPECIFIC GRAVITY VALUES: = 1.0300  
SPECIFIC GRAVITY TEXT: =1.03

VAPOR DENSITY TEXT: HEAVIER THAN AIR  
PERCENT VOLATILE BY VOLUME: 80.0000  
PERCENT VOLATILE BY VOLUME TEXT: 80

EVAPORATION RATE TEXT: SLOWER THAN ETHER; NOT ESTABLISHED FOR MIXTURE

SOLUBILITY IN WATER TEXT: INSOLUBLE BUT DISPERSIBLE

PH OF PRODUCT IN SOLUTION WITH WATER/TEXT: 8.9

PH OF PRODUCT AS RECEIVED (NEAT)/VALUE: = 8.9000

APPEARANCE: OPAQUE (MILKY) LIQUID WITH CHARACTERISTIC ODOR.

PHYSICAL STATE: LIQ  
PHYSICAL STATE TEXT: LIQUID

SECTION 10: STABILITY & REACTIVITY  
-----

STABILITY INDICATOR: Y  
STABILITY - CONDITIONS TO AVOID: OPEN FLAME, SPARKS, EXCESSIVE HEAT  
(ABOVE 100F), AND/OR CONTACT WITH STRONG OXIDIZING AGENTS.  
STABILITY - TEXT: YES

INCOMPATIBLE MATERIALS: STRONG ACIDS AND/OR STRONG OXIDIZING AGENTS  
(LIKE PEROXIDE).

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE,  
ACRID FUMES.

HAZARDOUS POLYMERIZATION INDICATOR: N  
HAZARDOUS POLYMERIZATION TEXT: NO

SECTION 13: DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD: DISPOSAL METHOD MUST COMPLY WITH LOCAL, STATE  
AND FEDERAL REGULATIONS.

-----  
SECTION 16: OTHER INFORMATION  
-----

SPECIAL PROTECTION: N/A

SPECIAL PROTECTION (MECHANICAL): MECHANICAL 50 CFM

\*\*\* END OF DATA SHEET \*\*\*

