

MSDS DATA SHEET

Created on 11/17/2003

Part Number: 1051498

XX

CHEMISTRI 11/17/03

DISPLAY MATERIAL SAFETY DATA SHEET 11:25:09

SCREEN QA06__ KEY 0000947999,0000000018_____

FID#: 00048464 VER-DT: 10/26/87

SECTION 01: CHEMICAL PRODUCT & COMPANY ID

PRODUCT PRIMARY NAME: TRUNK SPATTER PAINT

PLANT SYNONYMS: GM TRUNK SPATTER PAINT

- > GRAY TRUNK PAINT
- > RECONDITIONING PAINT - GRAY AND WHITE
- > WHITE TRUNK PAINT
- > 1U-173
- > 1051498
- > 34313

MSDS SIGNED BY NAME: JAMES H. GUSTAFSON

MSDS SIGNED BY TITLE: CHIEF CHEMIST

SAFE USE CATEGORY AND DESCRIPTION: 02 -SOLVENTS - FLASH POINT: < 100 F

LAST UPDATED DATE: 1988-01-11

MANUFACTURER'S ID (MID): 000517789

MANUFACTURER'S NAME: BARRETT VARNISH CO

MANUFACTURER'S EMERGENCY PHONE NUMBER/TEXT: US 312-242-2462

MANUFACTURER'S MAILING ADDRESS:

1532 S 50TH COURT

CICERO IL 60650

US

CHEMICAL FAMILY NAME: PAINT/CHEMICAL COATING

MOLECULAR FORMULA: MIXTURE

SECTION 02: COMPOSITION & INGREDIENT INFO

| CAS# | FORMULATION | W/V | CHEMICAL NAME |
|-----------|--------------------|-----|------------------------------------|
| 000067561 | T 0.0000/ 0.0000% | W | METHANOL |
| 000074986 | = 12.0000/ 0.0000% | W | Propane |
| 000075285 | = 8.0000/ 0.0000% | W | PROPANE, 2-METHYL- |
| 000079107 | T 0.0000/ 0.0000% | W | ACRYLIC ACID |
| 000108883 | = 2.0000/ 0.0000% | W | TOLUENE |
| 000111900 | T 0.0000/ 0.0000% | W | ETHANOL, 2-(2-ETHOXYETHOXY)- |
| 007727437 | = 2.0000/ 0.0000% | W | BARIUM SULFATE |
| 007732185 | = 31.0000/ 0.0000% | W | WATER |
| 009003207 | = 9.0000/ 0.0000% | W | ACETIC ACID, VINYL ESTER, POLYMER |
| 009052613 | = 2.0000/ 0.0000% | W | Benzene, ethenylmethyl-, polymer w |
| * | | | ith 1,3-butadiene |
| 013463677 | = 2.0000/ 0.0000% | W | TITANIUM OXIDE |
| 063449398 | T 0.0000/ 0.0000% | W | CHLORINATED PARAFFIN |
| 064742898 | = 27.0000/ 0.0000% | W | Solvent naphtha, petroleum, light |
| * | | | aliph. |
| * | | | (hydrogenated tallow alkyl)dimethy |
| * | | | l, salts with hectorite |

THRESHOLD LIMIT VALUE: 300 PPM VM&P.

PERMISSIBLE EXPOSURE LIMIT: 500 PPM VM&P.

CERCLA (SUPERFUND) REPORTABLE QUANTITY (LBS): N.A.

SECTION 03: HAZARDS IDENTIFICATION

PRIMARY ENTRY ROUTE INDICATORS:

| | |
|--|---|
| SKIN PRIMARY ENTRY ROUTE INDICATOR = | Y |
| EYE PRIMARY ENTRY ROUTE INDICATOR = | N |
| INHALATION PRIMARY ENTRY ROUTE INDICATOR = | Y |
| INGESTION PRIMARY ENTRY ROUTE INDICATOR = | N |

EFFECTS OF OVEREXPOSURE: INHALATION MAY CAUSE HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, ACUTE UNCONSCIOUSNESS OR COMA. SKIN AND EYE CONTACT: IRRITATION. CHRONIC EXTENSIVE & CONTINUOUS OVEREXPOSURE MAY RESULT IN RESPIRATORY ALLERGIC SENSITIVITY.

ADDITIONAL HEALTH HAZARD DATA: CONTENTS ARE UNDER PRESSURE. FLAME EXTENSION (AEROSOL PACKAGE) - OVER 18 INCHES WITH FLASHBACK.

SECTION 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES - GENERAL: VAPOR: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. NOTIFY PHYSICIAN. SPLASH: (EYES) FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. REFER TO PHYSICIAN. SPLASH: SKIN, WASH WITH SOAP & WATER. REMOVE CONTAMINATED

SECTION 05: FIRE-FIGHTING MEASURES

FLAMMABLE LEL: = 0.90
FLAMMABLE UEL: = 6.00

EXTINGUISHING MEDIA: WATER FOG, CHEMICAL FOAM, DRY CHEMICAL OR CO2.

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED SURFACES.

NFPA CODES:

| | |
|--------------------------|---|
| NFPA FLAMMABILITY CODE = | 4 |
| NFPA HEALTH CODE = | 3 |
| NFPA REACTIVITY CODE = | 1 |

FLASH POINT TEMPS: = - 10.00F
FLASH POINT TEXT: -10F TCC AEROSOL
FLASH POINT METHOD: TCC

SECTION 06: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: USE NON-SPARKING TOOLS, MOP UP AND VENTILATE ADEQUATELY. AVOID SPARKS, OPEN FLAMES, STATIC ELECTRICITY. FLUSH AREA WITH WATER.

SECTION 07: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: AVOID STORAGE IN HIGH TEMPERATURE AREAS. DOT STORAGE CATEGORY: KEEP AWAY FROM SPARKS, OPEN FLAME, STATIC ELECTRICITY.

SECTION 7 - OTHER INFORMATION: DO NOT TAKE INTERNALLY, AVOID PROLONGED CONTACT WITH SKIN, GROUND CONTAINERS WHEN POURING. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

SECTION 08: EXPOSURE CONTROLS - PROTECTION

EYE PROTECTION: SAFETY EYEWEAR.

RESPIRATORY PROTECTION: IF TLV IS EXCEEDED, WEAR NIOSH APPROVED RESPIRATORY PROTECTION EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT: USE SOLVENT IMPERMEABLE GLOVES FOR PROLONGED OR REPEATED CONTACT. USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS. AVOID SKIN CONTACT. USE OF PROTECTIVE CLOTHING IS RECOMMENDED.

PROTECTIVE GLOVES (SPECIFY TYPE): SOLVENT IMPERMEABLE.

SECTION 09: PHYSICAL & CHEMICAL PROPERTIES

ANALYTICAL VOC WITHOUT WATER: N.A.

THEORETICAL VOC: 8.00 BY

BOILING POINT TEMPS: 100.00C TO 143.00C/ 212.00F TO 290.00F
BOILING POINT TEXT: 212F-290F

SPECIFIC GRAVITY VALUES: = 0.9600
SPECIFIC GRAVITY TEXT: =0.96

VAPOR DENSITY VALUES: 1.0000
VAPOR DENSITY TEXT: 1
VAPOR PRESSURE VALUES/UOM: 30.0000MMHG
VAPOR PRESSURE TEXT: 30 MM HG @ 20 C.

PERCENT VOLATILE BY VOLUME: 86.0000
PERCENT VOLATILE BY VOLUME TEXT: 86
PERCENT SOLID BY WEIGHT VALUES: 19.0000
PERCENT SOLID BY WEIGHT TEXT: 19
EVAPORATION RATE VALUES: 0.45
EVAPORATION RATE TEXT: .45

SOLUBILITY IN WATER VALUES/UOM: 5.0000
SOLUBILITY IN WATER TEXT: 5%

PH OF PRODUCT IN SOLUTION WITH WATER/TEXT: 6

PH OF PRODUCT AS RECEIVED (NEAT)/VALUE: = 6.0000

APPEARANCE: MULTICOLOR PAINT WITH CHARACTERISTIC HYDROCARBON ODOR.

PHYSICAL STATE: LIQ
PHYSICAL STATE TEXT: LIQUID

STABILITY INDICATOR: Y
STABILITY - CONDITIONS TO AVOID: NONE FORESEEABLE.
STABILITY - TEXT: YES

INCOMPATIBLE MATERIALS: NONE FORESEEABLE.

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING RELEASES CO, CO2.

HAZARDOUS POLYMERIZATION INDICATOR: N
HAZARDOUS POLYMERIZATION - CONDITIONS TO AVOID: NONE.
HAZARDOUS POLYMERIZATION TEXT: NO

SECTION 13: DISPOSAL CONSIDERATIONS

CONCERNING DISPOSAL. DO NOT INCINERATE CLOSED CONTAINERS.

SECTION 14: TRANSPORT INFORMATION

DOT INFORMATION: SID NO. 13160 INCLUDES PAINT, LAQUER, ENAMEL, STAIN, SHELLAC, VARNISH, LIQUID ALUMINUM, LIQUID BRONZE, LIQUID GOLD, LIQUID WOOD FILLER, AND LIQUID LAQUER BASE. SEE ALSO SID NO. 13150, 'PAINT RELATED MATERIAL'.

SHIPPING NAME: PAINT

HAZARD CLASS: S:COMBUSTIBLE LIQUID H:FLAMMABLE LIQUID

U.N. CODE: UN1263UN1263

SECTION 16: OTHER INFORMATION

RCRA HAZARDOUS WASTE NUMBER TEXT: N.A.

LOCAL EXHAUST: SUFFICIENT TO KEEP STATED TLV & LEL IN SECTION II BELOW STATED LIMIT.

*** END OF DATA SHEET ***