

MSDS DATA SHEET

Created on 10/06/2003

Part Number: 12345117

XX

CHEMISTRI 10/06/03

DISPLAY MATERIAL SAFETY DATA SHEET 16:07:42

SCREEN QA06__ KEY 0000939732,0000000018_____

FID#: 00190035 VER-DT: 07/28/94

SECTION 01: CHEMICAL PRODUCT & COMPANY ID

PRODUCT PRIMARY NAME: AEROSOL SCRATCH FILLER & PRIMER FP-101

PLANT SYNONYMS: FP-101

- > GOODWRENCH SCRATCH FILLER AND PRIMER
- > SCRATCH FILLER & PRIMER
- > 12345117
- > 460 NITROCELLULOSE LACQUER

SAFE USE CATEGORY AND DESCRIPTION: 02 -SOLVENTS - FLASH POINT: < 100 F

LAST UPDATED DATE: 1994-07-28

MANUFACTURER'S ID (MID): 000501158
 MANUFACTURER'S NAME: DUPLI-COLOR PROD. CO.
 MANUFACTURER'S MAILING ADDRESS:
 1601 NICHOLAS BLVD
 SUBSIDIARY OF SHERWIN WILLIAMS
 ELK GROVE VILLAGE IL 60007
 US

SECTION 02: COMPOSITION & INGREDIENT INFO

CAS#	FORMULATION	W/V	CHEMICAL NAME
000067561	< 0.0000/ 3.0000%	W	METHANOL
000067641	= 31.0000/ 0.0000%	W	ACETONE
000074986	= 11.0000/ 0.0000%	W	PROPANE
000075285	= 11.0000/ 0.0000%	W	PROPANE, 2-METHYL-
000078933	= 12.0000/ 0.0000%	W	2-BUTANONE
000108883	< 0.0000/ 3.0000%	W	TOLUENE
000763699	= 6.0000/ 0.0000%	W	PROPIONIC ACID, 3-ETHOXY-, ETHYL E
*	STER		
001309371	= 5.0000/ 0.0000%	W	IRON(III) OXIDE
001330785	> 3.0000/ 0.0000%	W	PHOSPHORIC ACID, TRITOLYL ESTER
007631869	= 5.0000/ 0.0000%	W	Silica
009004700	< 0.0000/ 3.0000%	W	NITROCELLULOSE
989973951	= 4.0000/ 0.0000%	W	ALKYD RESIN

THRESHOLD LIMIT VALUE: METHANOL: 200 PPM; 260 MG/M3; ACETONE: 750 PPM; 1780 MG/M3; METHYL ETHYL KETONE: 200 PPM; 590 MG/M3; TOLUOL: 100 PPM; 375 MG/M3; MAGNESIUM SILICATE: 10 MG/M3; TALC: 10 MG/M3; PROPANE: 1000 PPM; 1800 MG/M3; ISOBUTANE: 1000 PPM; 1800 MG/M3

PERMISSIBLE EXPOSURE LIMIT: METHANOL: 200 PPM; ACETONE: 750 PPM; METHYL ETHYL KETONE: 200 PPM; TOLUOL: 100 PPM PROPANE: 1000 PPM; ISOBUTANE: 1000 PPM

SECTION 03: HAZARDS IDENTIFICATION

PRIMARY ENTRY ROUTE INDICATORS:

INHALATION PRIMARY ENTRY ROUTE INDICATOR = Y

INGESTION PRIMARY ENTRY ROUTE INDICATOR = Y

EFFECTS OF OVEREXPOSURE: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATIONS ARE ANESTHETIC. OVEREXPOSURE MAY RESULT IN LIGHTEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. IS ALSO AN IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. // CONTAINS PETROLEUM DISTILLATES - HARMFUL OR FATAL IF SWALLOWED. // CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE ESTABLISHED.

EMERGENCY FIRST AID PROCEDURES - SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE RE-USE.

EMERGENCY FIRST AID PROCEDURES - EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

EMERGENCY FIRST AID PROCEDURES - INHALATION: REMOVE PATIENT TO FRESH AIR

EMERGENCY FIRST AID PROCEDURES - INGESTION: CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

SECTION 05: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: CARBON DIOXIDE OR FOAM.

SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER MAY BE INEFFECTIVE ON FIRE BUT CAN BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: DO NOT USE NEAR OPEN FLAMES. DO NOT PUNCTURE CONTAINERS. CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

NFPA CODES:

NFPA FLAMMABILITY CODE = 3

NFPA HEALTH CODE = 3

NFPA REACTIVITY CODE = 1

FLASH POINT TEXT: PROPELLANT BELOW 20 DEG F; EXTREMELY FLAMMABLE.

FLASH POINT METHOD: TOC

SECTION 5 - OTHER INFORMATION: THE FOLLOWING ARE CHEMICAL NAMES AND ACETONE: 2.6; METHYL ETHYL KETONE: 1.8; TOLUOL: 1.3; PROPANE: 2.3 AND ISOBUTANE: 1.8.

SECTION 06: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

SECTION 07: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: USE ONLY WITH ADEQUATE VENTILATION, AVOID BREATHING VAPOR. AVOID CONTACT WITH SKIN AND EYES. WASH HANDS AFTER USING. PROTECT AGAINST DUST WHICH MAY BE GENERATED BY SANDING OR ABRADING THE DRIED FILM.. // VAPORS MAY IGNITE EXPLOSIVELY. SOURCES. DO NOT SMOKE. TURN OFF PILOT LIGHTS, STOVES, HEATERS, ELECTRIC MOTORS, AND OTHER SOURCES OF IGNITION DURING USE AND UNTIL ALL VAPORS

ARE GONE. DO NOT INCINERATE (BURN) CONTAINER. DO NOT EXPOSE TO HEAT OR STORE AT TEMPERATURES ABOVE 120 DEGREES F. DO NOT DISCARD EMPTY CONTAINER IN HOME GARBAGE COMPACTOR.

SECTION 7 - OTHER INFORMATION: OTHER PRECAUTIONS INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. KEEP AWAY FROM CHILDREN.

SECTION 08: EXPOSURE CONTROLS - PROTECTION

EYE PROTECTION: WEAR CHEMICAL SPLASH GOGGLES, FACE SHIELD, OR SAFETY SPECTACLES WITH UNPERFORATED SIDE SHIELDS.

DOORS OR USE OTHER MEANS TO INSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. IF YOU EXPERIENCE EYE WATERING, HEADACHES OR DIZZINESS, INCREASE FRESH AIR OR WEAR RESPIRATORY PROTECTION (NIOSH/MSHA TC 23C OR (EQUIVALENT) OR LEAVE THE AREA.

VENTILATION: LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IS MAINTAINED BELOW APPLICABLE LIMITS.

SECTION 8 - OTHER INFORMATION: REQUESTED A MORE SPECIFIC GLOVE TYPE; AWAITING RESPONSE FROM MANUFACTURER.

PROTECTIVE GLOVES (SPECIFY TYPE): IF DESIRED, WEAR SOLVENT RESISTANT GLOVES.

SECTION 09: PHYSICAL & CHEMICAL PROPERTIES
BOILING POINT TEMPS: < 26.00F

SPECIFIC GRAVITY VALUES: < 1.0000

VAPOR DENSITY VALUES: > 1.0000
VAPOR PRESSURE TEXT: 2280 MMHG

PERCENT VOLATILE BY WEIGHT TEXT: +/- 85 (BY VOLUME)

EVAPORATION RATE VALUES: < 1.00

SOLUBILITY IN WATER TEXT: NONE

APPEARANCE: TYPICAL OF PAINT AND LACQUER

ODOR: TYPICAL OF PAINT AND LACQUER

SECTION 9 - OTHER INFORMATION: AEROSOL CONTENTS UNDER PRESSURE OF 52 +/- PSIG

SECTION 10: STABILITY & REACTIVITY

STABILITY - TEXT: STABLE

HAZARDOUS DECOMPOSITION PRODUCTS: BY FIRE, CARBON DIOXIDE AND CARBON MONOXIDE

HAZARDOUS POLYMERIZATION TEXT: WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

THE NATIONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER, OR THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: DO NOT BURN OR INCINERATE. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

SECTION 14: TRANSPORT INFORMATION

HAZARD CLASS: CONSUMER COMMODITY, ORM-D

SECTION 15 - OTHER INFORMATION: PURSUANT TO CALIFORNIA PROPOSITION 65: CERTAIN RAW MATERIALS USED IN MAKING THIS PRODUCT CONTAIN SMALL AMOUNTS OF MATERIALS AS IMPURITIES WHICH ARE REGULATED BY PROPOSITION 65.

*** END OF DATA SHEET ***