
SECTION 01: CHEMICAL PRODUCT & COMPANY ID

PRODUCT PRIMARY NAME: AC GENERAL PURPOSE LUBRICANT ST-800
ALL SYNONYMS : AC GENERAL PURPOSE LUBRICANT ST-800
AC GENERAL PURPOSE LUBRICANT ST800
AC TYPE ST800
AC8595
DISCONTINUED 1997
GENERAL PURPOSE LUBRICANT
PETROLEUM HYDROCARBONS PLUS ADDITIVES
SA 825 8035
SA8258035
ST-800
ST-800 LUBRICANT
ST800
0498-1099
25033356
2633
304765 (OLD FID)
550807 INACTIVE

SAFE USE CATEGORY AND DESCRIPTION: 04 -METAL WORKING FLUIDS AND LUBRICANTS

LAST UPDATED DATE: 1986-01-01

MANUFACTURER'S ID (MID): 000550283
MANUFACTURER'S NAME: EXXON CO., USA (FORMER SOUTHWEST PETRO)
MANUFACTURER'S EMERGENCY PHONE NUMBER/TEXT: US 913-782-5800
MANUFACTURER'S MAILING ADDRESS:
ALSO SEE GMBA #519500 (EXXON)
1400 S. HARRISON
OLATHE KS 66061
US

CHEMICAL FAMILY NAME: PETROLEUM HYDROCARBON

MOLECULAR FORMULA: N/A

SECTION 02: COMPOSITION & INGREDIENT INFO

CAS#	FORMULATION	W/V	CHEMICAL NAME
008012951	R 84.0000/ 88.0000%	W	MINERAL OIL
009003310	R 2.0000/ 3.0000%	W	1,3-Butadiene, 2-methyl-, homopolymer
061790485	= 0.9900/ 0.0000%	W	Sulfonic acids, petroleum, barium salts
989918938	R 1.0000/ 2.0000%	W	ACRYLIC COPOLYMERS
989923427	< 0.0000/ 0.5000%	W	AROMATIC AMINES
989935929	< 0.0000/ 1.0000%	W	LITHIUM NAPHTHENATE

989953927 R 7.0000/ 9.0000% W LITHIUM FATTY ACID SOAP

THRESHOLD LIMIT VALUE: N/D

SECTION 03: HAZARDS IDENTIFICATION

PRIMARY ENTRY ROUTE INDICATORS:

SKIN PRIMARY ENTRY ROUTE INDICATOR =	N
EYE PRIMARY ENTRY ROUTE INDICATOR =	N
INHALATION PRIMARY ENTRY ROUTE INDICATOR =	N
INGESTION PRIMARY ENTRY ROUTE INDICATOR =	N

EFFECTS OF OVEREXPOSURE: MAY CAUSE SKIN AND EYE IRRITATION WITH PROLONGED CONTACT.

SECTION 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES - GENERAL: EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN IMMEDIATELY. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. INGESTION: CALL A PHYSICIAN IMMEDIATELY.

SECTION 05: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG, SAND, EARTH.

SPECIAL FIRE FIGHTING PROCEDURES: FIREFIGHTERS SHOULD WEAR AN APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: DENSE SMOKE.

NFPA CODES:

NFPA FLAMMABILITY CODE =	1
NFPA HEALTH CODE =	2
NFPA REACTIVITY CODE =	1

FLASH POINT TEMPS: > 160.00C/ 320.00F

FLASH POINT TEXT: >320F/160C COC

FLASH POINT METHOD: COC

SECTION 06: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: TRANSFER BULK OF MATERIAL INTO ANOTHER CONTAINER. ABSORB REMAINING RESIDUE WITH PROPER ABSORBENTS SUCH AS SAND, EARTH, VERMICULITE. SWEEP UP AND DISPOSE AS SOLID WASTE.

SECTION 07: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP CONTAINERS CLOSED. AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. WASH CLOTHING BEFORE REUSE. KEEP AWAY FROM FEED AND FOOD PRODUCTS.

SECTION 7 - OTHER INFORMATION: KEEP OUT OF REACH OF CHILDREN.

SECTION 08: EXPOSURE CONTROLS - PROTECTION

EYE PROTECTION: SAFETY GOGGLES AND FULL FACE SHIELD

RESPIRATORY PROTECTION: NONE REQUIRED

PERSONAL PROTECTIVE EQUIPMENT: NONE REQUIRED

PROTECTIVE GLOVES (SPECIFY TYPE): OIL RESISTANT RUBBER OR PLASTIC GLOVES

SECTION 09: PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT TEXT: NOT/DETERMINED

SPECIFIC GRAVITY VALUES: = 0.9480

SPECIFIC GRAVITY TEXT: =0.948 (AT ROOM TEMPERATURE)

VAPOR PRESSURE TEXT: N/D

PERCENT VOLATILE BY VOLUME TEXT: N/A

EVAPORATION RATE TEXT: N/A

SOLUBILITY IN WATER VALUES/UOM: 25.0000

SOLUBILITY IN WATER TEXT: NEGLIGIBLE AT 25C

PH OF PRODUCT IN SOLUTION WITH WATER/TEXT: N/A

APPEARANCE: AMBER SEMI-SOLID / MINERAL OIL ODOR

PHYSICAL STATE: PAS

PHYSICAL STATE TEXT: PASTE

SECTION 10: STABILITY & REACTIVITY

STABILITY INDICATOR: Y

STABILITY - TEXT: YES

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS SUCH AS: CHROMIC ACID, HYDROGEN PEROXIDE, BROMINE.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE

HAZARDOUS POLYMERIZATION INDICATOR: N

HAZARDOUS POLYMERIZATION TEXT: NO

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION 16: OTHER INFORMATION

SPECIAL PROTECTION (MECHANICAL): NONE REQUIRED